

Amendments to the Claims

SUBS

1. (Currently Amended) A method of transmitting a  
2 communication from a first network entity to a second network entity, wherein the  
first network entity and the second network entity are coupled to a communication  
4 medium, comprising:  
receiving a communication from a process operating on a first network entity,  
6 wherein the communication is directed to a second network entity;  
~~distributing elements of said communication into multiple portions, each said~~  
8 ~~portion corresponding to one of a plurality of channels established to convey a~~  
~~communication between said first network entity and said second network entity;~~  
10 allotting individual elements of said communication among a plurality of  
channels established to convey a communication between said first network entity and  
12 said second network entity;  
sending a first allotment of elements ~~portion~~ of said communication on a first  
14 channel established on a first communication medium coupled to said first network  
entity and said second network entity; and  
16 sending a second allotment of elements ~~portion~~ of said communication on a  
second channel established on a second communication medium coupled to said first  
18 network entity and said second network entity;  
wherein said communication is transmitted to said second entity at a data rate  
20 in excess of one gigabit per second. "

2. (Cancelled)

3. (Currently Amended) The method of claim 1, wherein said  
2 communication is an Ethernet frame and wherein each of said multiple elements  
~~portions~~ of said communication comprises one or more bytes.

4. (Previously Presented) A method of transmitting a  
2 communication from a first network entity to a second network entity, wherein the  
first network entity and the second network entity are coupled to a communication  
4 medium, comprising:  
receiving a communication at a distribution module of a network interface

6 device from a medium access control module across a first interface, wherein said  
distribution module is configured to distribute portions of said communication among  
8 a plurality of communication channels;

distributing elements of said communication into multiple portions;

10 sending a first portion of said communication on a first channel established on  
a first communication medium coupled to said first network entity and said second  
12 network entity; and

sending a second portion of said communication on a second channel  
14 established on a second communication medium coupled to said first network entity  
and said second network entity.

5. (Original) The method of claim 4, wherein said first interface is  
2 configured to convey said communication at a data rate exceeding one gigabit per  
second.

6. (Original) The method of claim 4, in which said sending a first  
2 portion of said communication comprises forwarding an apportionment of said  
communication elements to a first physical coding module across a second interface;  
4 and  
wherein said first physical coding module is configured to encode said  
6 apportionment of communication elements into a series of codes for transmission over  
said first communication medium.

7. (Original) The method of claim 6, wherein said first physical  
2 coding module:  
encodes a first element of said apportionment with a first start code if said first  
4 element is the first element of said communication and otherwise encodes said first  
element of said apportionment with a second start code; and  
6 encodes a last element of said apportionment with a first end code if said last  
element is the last element of said communication and otherwise encodes said last  
8 element of said apportionment with a second end code.

8. (Original) The method of claim 6, wherein said second interface is  
2 configured to convey said first apportionment at a data rate exceeding one gigabit per

second.

9. (Previously Presented) The method of claim 4, in which said  
2 distributing comprises allotting elements of said communication among a plurality of  
channels established to convey a communication between said first network entity and  
4 said second network entity.

10. (Original) The method of claim 9, wherein each of said channels is  
2 configured to traverse a separate physical communication link.

11. (Original) The method of claim 9, wherein each of said channels is  
2 configured to traverse a common physical communication link, said common physical  
communication link comprising said first communication medium and said second  
4 communication medium.

12. (Previously Presented) The method of claim 4, wherein:  
2 one of said first portion of said communication and said second portion of said  
communication includes a first start symbol configured to indicate a start of said  
4 communication and the other of said first portion and said second portion includes a  
second start symbol configured to indicate a start of a portion of said communication;  
6 and  
one of said first portion of said communication and said second portion of said  
8 communication includes a first end symbol configured to indicate an end of said  
communication and the other of said first portion and said second portion includes a  
10 second end symbol configured to indicate an end of a portion of said communication.

13. (Previously Presented) The method of claim 4, further  
2 comprising:  
transmitting a first idle signal on said first channel and said second channel  
4 prior to said receiving; and  
transmitting a different idle signal on said first channel and said second  
6 channel after said sending a second portion of said communication.

14. (Previously Presented) The method of claim 4, further

2 comprising:

encoding the first element of said first portion of said communication with a  
4 first starting delimiter; and

encoding the first element of said second portion of said communication with  
6 a second starting delimiter.

15. (Original) The method of claim 14, further comprising:

2 encoding the last element of said first portion of said communication with a  
first ending delimiter; and

4 encoding the last element of said second portion of said communication with a  
second ending delimiter.

16. (Previously Presented) A method of receiving a communication  
2 at a second network entity from a first network entity, wherein the first network entity  
and the second network entity are coupled to a dedicated communication medium,  
4 comprising:

receiving at a second network entity a first idle code on each of multiple  
6 channels established between a first network and said second network entity;

receiving at said second network entity a first portion of a communication  
8 from said first network entity on a first channel of said multiple channels;

receiving at said second network entity a second portion of said  
10 communication on a second channel of said multiple channels;

collecting an element of said first portion and an element of said second  
12 portion;

receiving at said second network entity a second idle code, different from said  
14 first idle code, on each of said multiple channels; and

forwarding said communication toward a process operating on said second  
16 network entity.

17. (Original) The method of claim 16, wherein said communication is  
2 an Ethernet frame.

18. (Previously Presented) The method of claim 17, wherein said  
2 first portion of a communication comprises:

4 a first start signal configured to indicate a beginning of said communication;  
and  
a first set of elements of said communication.

19. (Previously Presented) The method of claim 18, wherein said  
2 second portion of a communication comprises:

4 a second start signal configured to indicate a beginning of a portion of said  
communication, said second start signal differing from said first start signal; and  
a second set of elements of said communication.

20. (Original) The method of claim 16, wherein said first  
2 communication channel and said second communication channel traverse a common  
communication medium.

21. (Original) The method of claim 16, wherein said first  
2 communication channel and said second communication channel traverse separate  
physical mediums.

22. (Original) The method of claim 16, in which said collecting  
2 comprises:  
receiving at a collection module an element of said first communication  
4 portion and an element of said second communication portion; and  
combining said element of said first communication portion and said element  
6 of said second communication portion.

23. (Previously Presented) A method of receiving a communication  
2 at a second network entity from a first network entity, wherein the first network entity  
and the second network entity are coupled to a dedicated communication medium,  
4 comprising:  
receiving at a second network entity a first portion of a communication from a  
6 first network entity on a first channel established between said first network entity and  
said second network entity;

8 receiving at said second network entity a second portion of said  
communication on a second channel established between said first network entity and  
10 said second network entity;

receiving at a collection module an element of said first communication  
12 portion and an element of said second communication portion;

combining said element of said first communication portion and said element  
14 of said second communication portion; and

sending said combined elements to a medium access control module across a  
16 first interface toward a process operating on said second network entity.

24. (Original) The method of claim 23, wherein said first interface is  
2 configured to convey said combined elements at a data rate greater than one gigabit  
per second.

25. (Previously Presented) The method of claim 23, further  
2 comprising:  
receiving a first idle code on each of said first channel and said second channel  
4 prior to said receiving a first portion of a communication; and  
receiving a second idle code on each of said first channel and said second  
6 channel after said receiving a second portion of said communication.

26. (Cancelled)

27. (Cancelled)

28. (Original) A method of receiving a communication from a first  
2 network entity at a second network entity across a plurality of channels, comprising:  
receiving synchronization information across each of a plurality of channels  
4 coupling a first network entity to a second network entity;  
receiving at said second network entity a set of bytes across each of said  
6 channels;  
detecting a first byte and a last byte in each of said sets of bytes;  
8 decoding each of said sets of bytes; and  
re-assembling said sets of bytes into a stream of bytes of a communication

10 directed from said first network entity to said second network entity.

29. (Original) The method of claim 28, in which:

2 said receiving synchronization information comprises receiving a first idle  
code on each of said channels; and

4 wherein said method further comprises receiving a second idle code on each of  
said channels after said receiving a set of bytes across each of said channels.

30. (Previously Presented) A method of operating a computer to  
2 communicate with a network entity, comprising:

operating a medium access control module configured to communicate a first  
4 frame from a computer system to a network entity and receive a second frame at said  
computer system from said network entity;

6 operating a distribution module to apportion contents of said first frame  
among a plurality of communication channels coupling said computer system to said  
8 network entity through one or more communication links; and

operating a collection module to combine contents of said second frame  
10 received through said plurality of communication channels;

12 wherein said distribution module and said collection module interface with  
each of said communication channels at a rate exceeding one gigabit per second; and

14 wherein said medium access control module interfaces with said distribution  
module and said collection module at a rate substantially equal to the sum of said  
rates at which said communication channels interface with said distribution module  
16 and said collection module.

31. (Original) The method of claim 30, further comprising:

2 operating a physical medium module configured to encode said first frame  
contents for transmission over said communication channels and decode said second  
4 frame contents received over said communication channels.

32. (Cancelled)

33. (Previously Presented) The method of claim 30, wherein said  
2 first frame is a communication frame configured for transmission over a network

Al  
Cont.

compatible with an Ethernet communication protocol.

34. (Original) A network interface device for coupling a computer  
2 system to a network, comprising:  
a medium access control module configured to communicate with an  
4 application executing on a computer system;  
multiple physical coding modules, wherein each said physical coding module  
6 is configured to encode packet bytes for transmission on a network medium and  
decode encoded bytes received from said network medium, and wherein said network  
8 medium is configured to carry said bytes between said computer system and a  
network entity;  
10 a distributor configured to accept a first packet from said medium access  
control module and divide said first packet into a first plurality of packet bytes for  
12 transmission across said network medium; and  
a collector configured to accept a second plurality of packet bytes from said  
14 multiple physical coding modules and combine said second plurality of packet bytes  
into a second packet for transfer to said medium access control module.

35. (Original) The network interface device of claim 34, further  
2 comprising a first set of interfaces coupling said multiple physical coding modules to  
said distributor and said collector, wherein each of said first set of interfaces is  
4 configured to operate at a rate exceeding one gigabit per second.

36. (Original) The network interface device of claim 35, further  
2 comprising a second interface coupling said distributor and said collector to said  
medium access control module, wherein said second interface is configured to operate  
4 at a rate approximately equal to the sum of said operation rates of said first set of  
interfaces.

37. (Previously Presented) The network interface device of claim  
2 36, wherein said second interface is configured to operate at a data rate of  
approximately ten gigabits per second.

38. (Cancelled)



11 Cont.

39. (Previously Presented) A device for implementing an Ethernet  
2 protocol to communicate Ethernet frames between a first network entity and a second  
network entity, comprising:  
4 a distributor configured to distribute bytes of a first Ethernet frame over a  
plurality of channels in a first order;  
6 a collector configured to receive bytes of a second Ethernet frame over said  
channels in a second order;  
8 a first interface coupling said distributor and said collector to a medium access  
control module at a data rate exceeding one gigabit per second, wherein data are  
10 transferred across said first interface in multi-byte units in synchronization with both  
edges of a clock signal; and  
12 a second interface coupling said distributor and said collector to a first  
physical coding module at a data rate exceeding one gigabit per second in  
14 synchronization with both edges of a second clock signal.

40. (Previously Presented) The device of claim 39, wherein said  
2 first order and said second order are round robin.

41. (Currently Amended) The method of claim 1, wherein:  
2 said receiving comprises receiving a communication at a distribution module  
of a network interface device from a medium access control module across a first  
4 interface; and  
said distribution module is configured to perform said allotting of elements  
6 ~~distribution of said portions~~ of said communication among said plurality of  
communication channels, including said first channel and said second channel.

42. (Previously Presented) The method of claim 41, wherein said  
2 first interface is configured to convey said communication at a data rate exceeding  
one gigabit per second.

43. (Currently Amended) The method of claim 41, in which said  
2 sending a first allotment of elements ~~portion~~ of said communication comprises  
forwarding an apportionment of said communication elements to a first physical

4 coding module across a second interface; and  
wherein said first physical coding module is configured to encode said  
6 apportionment of communication elements with a series of codes for transmission  
over said first communication medium.

44. (Previously Presented) The method of claim 43, wherein said  
2 first physical coding module:  
encodes a first element of said apportionment with a first start code if said first  
4 element is the first element of said communication and otherwise encodes said first  
element of said apportionment with a second start code; and  
6 encodes a last element of said apportionment with a first end code if said last  
element is the last element of said communication and otherwise encodes said last  
8 element of said apportionment with a second end code.

45. (Previously Presented) The method of claim 43, wherein said  
2 second interface is configured to convey said apportionment at a data rate exceeding  
one gigabit per second.

46. (Cancelled)

47. (Currently Amended) The method of claim 1, wherein:  
2 one of said first allotment of elements ~~portion~~ of said communication and said  
second allotment of elements ~~portion~~ of said communication includes a first start  
4 symbol configured to indicate a start of said communication and the other of said first  
allotment ~~portion~~ and said second allotment ~~portion~~ includes a second start symbol  
6 configured to indicate a start of a portion of said communication; and  
one of said first allotment of elements ~~portion~~ of said communication and said  
8 second allotment of elements ~~portion~~ of said communication includes a first end  
symbol configured to indicate an end of said communication and the other of said first  
10 allotment ~~portion~~ and said second allotment ~~portion~~ includes a second end symbol  
configured to indicate an end of a portion of said communication.

Sub 1  
2 48. (Currently Amended) The method of claim 1, further  
comprising:

transmitting a first idle signal on said first channel and said second channel  
4 prior to said receiving; and  
transmitting a second idle signal on said first channel and said second channel  
6 after said sending said second allotment of elements ~~a second portion~~ of said  
communication;  
8 wherein said second idle signal is different from said first idle signal.

49. (Currently Amended) The method of claim 1, further  
2 comprising:  
encoding the first element of said first allotment of elements portion of said  
4 communication with a first starting delimiter; and  
encoding the first element of said second allotment of elements portion of said  
6 communication with a second starting delimiter;  
wherein said second starting delimiter is different from said first starting  
8 delimiter.

50. (Currently Amended) The method of claim 49, further  
2 comprising:  
encoding the last element of said first allotment of elements portion of said  
4 communication with a first ending delimiter; and  
encoding the last element of said second allotment of elements portion of said  
6 communication with a second ending delimiter;  
wherein said second ending delimiter is different from said first ending  
8 delimiter.

51. (Currently Amended) A computer readable storage medium  
2 storing instructions that, when executed by a computer, cause the computer to perform  
a method of transmitting a communication from a first network entity to a second  
4 network entity, the method comprising:  
receiving a communication from a process operating on a first network entity,  
6 wherein the communication is directed to a second network entity;  
~~distributing elements of said communication into multiple portions, each said~~  
8 ~~portion corresponding to one of a plurality of channels established to convey a~~  
~~communication between said first network entity and said second network entity;~~

10 allotting individual elements of said communication among a plurality of  
12 channels established to convey a communication between said first network entity and  
12 said second network entity;

14 sending a first allotment of elements ~~portion~~ of said communication on a first  
14 channel established on a first communication medium coupled to said first network  
entity and said second network entity; and

16 sending a second allotment of elements ~~portion~~ of said communication on a  
18 second channel established on a second communication medium coupled to said first  
18 network entity and said second network entity;

20 wherein said communication is transmitted to said second entity at a data rate  
in excess of one gigabit per second.

52. (Previously Presented) The method of claim 4, wherein said  
2 communication is transmitted to said second entity at a data rate in excess of one  
gigabit per second.

53. (Previously Presented) The method of claim 4, wherein said  
2 communication is an Ethernet frame and wherein each of said multiple portions of  
said communication comprises one or more bytes.

54. (Previously Presented) A computer readable storage medium  
2 storing instructions that, when executed by a computer, cause the computer to perform  
a method of transmitting a communication from a first network entity to a second  
4 network entity, the method comprising:

6 receiving a communication at a distribution module of a network interface  
6 device from a medium access control module across a first interface, wherein said  
distribution module is configured to distribute portions of said communication among  
8 a plurality of communication channels;

10 distributing elements of said communication into multiple portions;  
10 sending a first portion of said communication on a first channel established on  
a first communication medium coupled to said first network entity and said second  
12 network entity; and

14 sending a second portion of said communication on a second channel  
established on a second communication medium coupled to said first network entity

and said second network entity.

55. (Previously Presented) The method of claim 22, wherein said forwarding comprises sending said combined elements to a medium access control module across a first interface toward a process operating on said second network entity.

56. (Previously Presented) The method of claim 55, wherein said first interface is configured to convey said combined elements at a data rate greater than one gigabit per second.

57. (Previously Presented) A computer readable storage medium storing instructions that, when executed by a computer, cause the computer to perform a method of receiving a communication at a second network entity from a first network entity, the method comprising:

receiving at a second network entity a first idle code on each of multiple channels established between a first network and said second network entity;

receiving at said second network entity a first portion of a communication from said first network entity on a first channel of said multiple channels;

receiving at said second network entity a second portion of said communication on a second channel of said multiple channels;

collecting an element of said first portion and an element of said second portion;

receiving at said second network entity a second idle code, different from said first idle code, on each of said multiple channels; and

forwarding said communication toward a process operating on said second network entity.

58. (Previously Presented) The method of claim 23, wherein said communication is an Ethernet frame.

59. (Previously Presented) The method of claim 23, wherein said first portion of a communication comprises:

4 and  
a first start signal configured to indicate a beginning of said communication;  
a first set of elements of said communication.

60. (Previously Presented) The method of claim 59, wherein said  
2 second portion of a communication comprises:

a second start signal configured to indicate a beginning of a portion of said  
4 communication, said second start signal differing from said first start signal; and  
a second set of elements of said communication.

61. (Previously Presented) A computer readable storage medium  
2 storing instructions that, when executed by a computer, cause the computer to perform  
a method of receiving a communication at a second network entity from a first  
4 network entity, the method comprising:

receiving at a second network entity a first portion of a communication from a  
6 first network entity on a first channel established between said first network entity and  
said second network entity;

8 receiving at said second network entity a second portion of said  
communication on a second channel established between said first network entity and  
10 said second network entity;

receiving at a collection module an element of said first communication  
12 portion and an element of said second communication portion;

combining said element of said first communication portion and said element  
14 of said second communication portion; and

sending said combined elements to a medium access control module across a  
16 first interface toward a process operating on said second network entity.

62. (Previously Presented) The method of claim 28, wherein:  
2 the communication is a packet; and  
said receiving a set of bytes comprises receiving across each said channel a  
4 mini-frame comprising a portion of the packet.

63. (Previously Presented) The method of claim 62, wherein said  
2 detecting comprises:

on a first of said channels, identifying a start of packet delimiter; and  
4 on the other channels of said channels, identifying a start of mini-frame  
delimiter.

64. (Previously Presented) The method of claim 62, wherein said  
2 detecting comprises:

on a first of said channels, identifying an end of packet delimiter; and  
4 on the other channels of said channels, identifying an end of mini-frame  
delimiter.

65. (Previously Presented) The method of claim 62, wherein:  
2 said re-assembling comprises merging said mini-frames to re-form the packet;  
and  
4 the method further comprises forwarding the packet toward a medium access  
control module.

66. (Previously Presented) The method of claim 28, wherein each  
2 said set of bytes is received at a data rate exceeding one gigabit per second.

67. (Previously Presented) The method of claim 28, wherein said  
2 decoding comprises:  
at a physical coding module coupled to each of said channels, decoding a set  
4 of bytes from codes received over said channel.

68. (Previously Presented) A computer readable storage medium  
2 storing instructions that, when executed by a computer, cause the computer to perform  
a method of receiving a communication from a first network entity at a second  
4 network entity across a plurality of channels, the method comprising:  
receiving synchronization information across each of a plurality of channels  
6 coupling a first network entity to a second network entity;  
receiving at said second network entity a set of bytes across each of said  
8 channels;  
detecting a first byte and a last byte in each of said sets of bytes;  
10 decoding each of said sets of bytes; and

re-assembling said sets of bytes into a stream of bytes of a communication  
12 directed from said first network entity to said second network entity.

69. (Previously Presented) The method of claim 30, wherein said  
2 distribution module apportions said contents of said first frame by:  
receiving a portion of said first frame from said medium access control  
4 module; and  
distributing said portion of said first frame among said plurality of  
6 communication channels in round robin order.

70. (Previously Presented) The method of claim 30, wherein said  
2 collection module combines said contents of said second frame by:  
merging, in round robin order, segments of said second frame received from  
4 said plurality of communication channels; and  
forwarding said merged segments to said medium access control module.

71. (Previously Presented) A computer readable storage medium  
2 storing instructions that, when executed by a computer, cause the computer to perform  
a method of operating a computer to communicate with a network entity, the method  
4 comprising:  
operating a medium access control module configured to communicate a first  
6 frame from a computer system to a network entity and receive a second frame at said  
computer system from said network entity;  
8 operating a distribution module to apportion contents of said first frame  
among a plurality of communication channels coupling said computer system to said  
10 network entity through one or more communication links; and  
operating a collection module to combine contents of said second frame  
12 received through said plurality of communication channels;  
wherein said distribution module and said collection module interface with  
14 each of said communication channels at a rate exceeding one gigabit per second; and  
wherein said medium access control module interfaces with said distribution  
16 module and said collection module at a rate substantially equal to the sum of said  
rates at which said communication channels interface with said distribution module  
18 and said collection module.



72. (Previously Presented) A method of transmitting a  
2 communication from a first network entity to a second network entity, wherein the  
first network entity and the second network entity are coupled to a communication  
4 medium, comprising:  
receiving a communication from a process operating on a first network entity,  
6 wherein the communication is directed to a second network entity;  
distributing elements of said communication into multiple portions;  
8 sending a first portion of said communication on a first channel established on  
a first communication medium coupled to said first network entity and said second  
10 network entity; and  
sending a second portion of said communication on a second channel  
12 established on a second communication medium coupled to said first network entity  
and said second network entity;  
14 wherein said communication is transmitted to said second entity at a data rate  
in excess of one gigabit per second; and  
16 wherein one of said first portion of said communication and said second  
portion of said communication includes a first start symbol configured to indicate a  
18 start of said communication and the other of said first portion and said second portion  
includes a second start symbol configured to indicate a start of a portion of said  
20 communication; and  
wherein one of said first portion of said communication and said second  
22 portion of said communication includes a first end symbol configured to indicate an  
end of said communication and the other of said first portion and said second portion  
24 includes a second end symbol configured to indicate an end of a portion of said  
communication.

73. (Previously Presented) The method of claim 72, wherein:  
2 said receiving comprises receiving a communication at a distribution module  
of a network interface device from a medium access control module across a first  
4 interface; and  
said distribution module is configured to distribute portions of said  
6 communication among a plurality of communication channels, including said first  
channel and said second channel.

74. (Previously Presented) The method of claim 73, wherein said  
2 first interface is configured to convey said communication at a data rate exceeding  
one gigabit per second.

75. (Previously Presented) The method of claim 73, in which said  
2 sending a first portion of said communication comprises forwarding an apportionment  
of said communication elements to a first physical coding module across a second  
4 interface; and

wherein said first physical coding module is configured to encode said  
6 apportionment of communication elements into a series of codes for transmission over  
said first communication medium.

76. (Previously Presented) The method of claim 75, wherein said  
2 first physical coding module:

encodes a first element of said apportionment with a first start code if said first  
4 element is the first element of said communication and otherwise encodes said first  
element of said apportionment with a second start code; and

6 encodes a last element of said apportionment with a first end code if said last  
element is the last element of said communication and otherwise encodes said last  
8 element of said apportionment with a second end code.

77. (Previously Presented) The method of claim 75, wherein said  
2 second interface is configured to convey said first apportionment at a data rate  
exceeding one gigabit per second.

78. (Previously Presented) The method of claim 72, in which said  
2 distributing comprises:

allotting elements of said communication among a plurality of channels  
4 established to convey a communication between said first network entity and said  
second network entity, including said first channel and said second channel.

79. (Previously Presented) The method of claim 72, further  
2 comprising:

transmitting a first idle signal on said first channel and said second channel  
4 prior to said receiving; and  
transmitting a second idle signal on said first channel and said second channel  
6 after said sending a second portion of said communication;  
wherein said second idle signal is different from said first idle signal.

80. (Previously Presented) The method of claim 72, further  
2 comprising:  
encoding the first element of said first portion of said communication with a  
4 first starting delimiter; and  
encoding the first element of said second portion of said communication with  
6 a second starting delimiter;  
wherein said second starting delimiter is different from said first starting  
8 delimiter.

81. (Previously Presented) The method of claim 80, further  
2 comprising:  
encoding the last element of said first portion of said communication with a  
4 first ending delimiter; and  
encoding the last element of said second portion of said communication with a  
6 second ending delimiter;  
wherein said second ending delimiter is different from said first ending  
8 delimiter.

82. (Previously Presented) A computer readable storage medium  
2 storing instructions that, when executed by a computer, cause the computer to perform  
a method of transmitting a communication from a first network entity to a second  
4 network entity, wherein the first network entity and the second network entity are  
coupled to a communication medium, the method comprising:  
6 receiving a communication from a process operating on a first network entity,  
wherein the communication is directed to a second network entity;  
8 distributing elements of said communication into multiple portions;  
sending a first portion of said communication on a first channel established on  
10 a first communication medium coupled to said first network entity and said second

network entity; and

12 sending a second portion of said communication on a second channel  
established on a second communication medium coupled to said first network entity  
14 and said second network entity;

wherein said communication is transmitted to said second entity at a data rate  
16 in excess of one gigabit per second; and

wherein one of said first portion of said communication and said second  
18 portion of said communication includes a first start symbol configured to indicate a  
start of said communication and the other of said first portion and said second portion  
20 includes a second start symbol configured to indicate a start of a portion of said  
communication; and

22 wherein one of said first portion of said communication and said second  
portion of said communication includes a first end symbol configured to indicate an  
24 end of said communication and the other of said first portion and said second portion  
includes a second end symbol configured to indicate an end of a portion of said  
26 communication.

83. (Previously Presented) A method of transmitting a  
2 communication from a first network entity to a second network entity, wherein the  
first network entity and the second network entity are coupled to a communication  
4 medium, comprising:

transmitting a first idle signal on:

6 a first channel established on a first communication medium coupled to  
said first network entity and said second network entity; and

8 a second channel established on a second communication medium  
coupled to said first network entity and said second network entity;

10 receiving a communication from a process operating on said first network  
entity, wherein the communication is directed to said second network entity;

12 distributing elements of said communication into multiple portions;

sending a first portion of said communication on said first channel;

14 sending a second portion of said communication on said second channel; and

transmitting a second idle signal on said first channel and said second channel  
16 after said sending a second portion of said communication, wherein said second idle  
signal is different from said first idle signal;

18 wherein said communication is transmitted to said second entity at a data rate  
in excess of one gigabit per second.

84. (Previously Presented) The method of claim 83, wherein:  
2 said receiving comprises receiving a communication at a distribution module  
of a network interface device from a medium access control module across a first  
4 interface; and  
said distribution module is configured to distribute portions of said,  
6 communication among a plurality of communication channels, including said first  
channel and said second channel.

85. (Previously Presented) The method of claim 84, wherein said  
2 first interface is configured to convey said communication at a data rate exceeding  
one gigabit per second.

86. (Previously Presented) The method of claim 84, in which said  
2 sending a first portion of said communication comprises forwarding an apportionment  
of said communication elements to a first physical coding module across a second  
4 interface; and  
wherein said first physical coding module is configured to encode said  
6 apportionment of communication elements into a series of codes for transmission over  
said first communication medium.

87. (Previously Presented) The method of claim 86, wherein said  
2 first physical coding module:  
encodes a first element of said apportionment with a first start code if said first  
4 element is the first element of said communication and otherwise encodes said first  
element of said apportionment with a second start code; and  
6 encodes a last element of said apportionment with a first end code if said last  
element is the last element of said communication and otherwise encodes said last  
8 element of said apportionment with a second end code.

88. (Previously Presented) The method of claim 86, wherein said  
2 second interface is configured to convey said first apportionment at a data rate

exceeding one gigabit per second.

2 89. (Previously Presented) The method of claim 83, in which said  
distributing comprises:

4 allotting elements of said communication among a plurality of channels  
established to convey a communication between said first network entity and said  
second network entity, including said first channel and said second channel.

2 90. (Previously Presented) The method of claim 83, wherein:  
one of said first portion of said communication and said second portion of said  
communication includes a first start symbol configured to indicate a start of said  
4 communication and the other of said first portion and said second portion includes a  
second start symbol configured to indicate a start of a portion of said communication;  
6 and

8 one of said first portion of said communication and said second portion of said  
communication includes a first end symbol configured to indicate an end of said  
communication and the other of said first portion and said second portion includes a  
10 second end symbol configured to indicate an end of a portion of said communication.

2 91. (Previously Presented) The method of claim 83, further  
comprising:  
encoding the first element of said first portion of said communication with a  
4 first starting delimiter; and  
encoding the first element of said second portion of said communication with  
6 a second starting delimiter;  
wherein said second starting delimiter is different from said first starting  
8 delimiter.

2 92. (Previously Presented) The method of claim 91, further  
comprising:  
encoding the last element of said first portion of said communication with a  
4 first ending delimiter; and  
encoding the last element of said second portion of said communication with a  
6 second ending delimiter;

wherein said second ending delimiter is different from said first ending  
8 delimiter.

93. (Previously Presented) The method of claim 83, wherein said  
2 sending a first portion of said communication comprises:  
encoding said first portion of said communication with a first start code if said  
4 first portion of said communication includes the initial byte of said communication.

94. (Previously Presented) The method of claim 93, wherein said  
2 sending a first portion of said communication further comprises:  
encoding said first portion of said communication with a second start code,  
4 different from said first start code, if said first portion of said communication does not  
include the initial byte of said communication.

95. (Previously Presented) The method of claim 93, wherein said  
2 sending a first portion of said communication further comprises:  
encoding said first portion of said communication without a start code if said  
4 first portion of said communication does not include the initial byte of said  
communication.

96. (Previously Presented) The method of claim 83, wherein said  
2 sending a second portion of said communication comprises:  
encoding said second portion of said communication with a first end code if  
4 said second portion of said communication includes the final byte of said  
communication.

97. (Previously Presented) The method of claim 96, wherein said  
2 sending a second portion of said communication further comprises:  
encoding said second portion of said communication with a second end code,  
4 different from said first end code, if said second portion of said communication does  
not include the final byte of said communication.

98. (Previously Presented) The method of claim 96, wherein said  
2 sending a second portion of said communication further comprises:

4 encoding said second portion of said communication without an end code if  
said second portion of said communication does not include the final byte of said  
communication.

99. (Previously Presented) A computer readable storage medium  
2 storing instructions that, when executed by a computer, cause the computer to perform  
a method of transmitting a communication from a first network entity to a second  
4 network entity, wherein the first network entity and the second network entity are  
coupled to a communication medium, the method comprising:  
6 transmitting a first idle signal on:  
a first channel established on a first communication medium coupled to  
8 said first network entity and said second network entity; and  
a second channel established on a second communication medium  
10 coupled to said first network entity and said second network entity;  
receiving a communication from a process operating on said first network  
12 entity, wherein the communication is directed to said second network entity;  
distributing elements of said communication into multiple portions;  
14 sending a first portion of said communication on said first channel;  
sending a second portion of said communication on said second channel; and  
16 transmitting a second idle signal on said first channel and said second channel  
after said sending a second portion of said communication, wherein said second idle  
18 signal is different from said first idle signal;  
wherein said communication is transmitted to said second entity at a data rate  
20 in excess of one gigabit per second.

100. (Previously Presented) The device of claim 39, wherein said  
2 distributor distributes a substantially equivalent number of bytes of the first Ethernet  
frame over each channel in said plurality of channels.

101. (Previously Presented) The device of claim 39, wherein said  
2 collector receives a substantially equivalent number of bytes of the second Ethernet  
frame over each channel in said plurality of channels.

102. (Previously Presented) The device of claim 39, further



2 comprising a separate physical coding module for each channel in said plurality of  
channels, including said first physical coding module corresponding to a first channel.

103. (Previously Presented) The device of claim 102, wherein each  
2 said physical coding module is configured to encode the bytes of the first Ethernet  
frame that are distributed over the corresponding channel in said plurality of channels.

104. (Previously Presented) The device of claim 39, wherein:  
2 a first idle is distributed over each channel in said plurality of channels before  
distributing the bytes of the first Ethernet frame; and  
4 a second idle, different from said first idle, is distributed over each channel in  
said plurality of channels after distributing the bytes of the first Ethernet frame.

105. (Previously Presented) The device of claim 39, wherein a first  
2 set of bytes of the first Ethernet frame that are distributed over a first channel in said  
plurality of channels are preceded by a start code if said first set of bytes includes the  
4 initial byte of the first Ethernet frame.

106. (Previously Presented) The device of claim 39, wherein bytes of  
2 the first Ethernet frame that are distributed over each channel in said plurality of  
channels are preceded by a start code.

107. (Previously Presented) The device of claim 106, wherein said  
2 start code is different for a first channel in said plurality of channels than for one or  
more other channels in said plurality of channels.

108. (Previously Presented) The device of claim 39, wherein a last  
2 set of bytes of the first Ethernet frame that are distributed over a last channel in said  
plurality of channels are followed by an end code if said last set of bytes includes the  
4 final byte of the first Ethernet frame.

109. (Previously Presented) The device of claim 39, wherein bytes of  
2 the first Ethernet frame that are distributed over each channel in said plurality of  
channels are followed by an end code.

110. (Previously Presented) The device of claim 109, wherein said  
2 end code is different for a first channel in said plurality of channels than for the other  
channels in said plurality of channels.

111. (Previously Presented) The device of claim 39, wherein each  
2 channel in said plurality of channel traverses a separate physical communication link  
between the first network entity and the second network entity.

112. (Previously Presented) The device of claim 39, wherein each  
2 channel in said plurality of channel traverses a common physical communication link  
between the first network entity and the second network entity.

113. (Previously Presented) The device of claim 39, wherein said  
2 collector is further configured to:  
combine the bytes to produce the second Ethernet frame; and  
4 forward the second Ethernet frame to the medium access control module.

114. (Previously Presented) The device of claim 39, wherein said  
2 clock signal and said second clock signal are the same clock signal.

115. (Previously Presented) The network interface device of claim  
2 34, wherein:  
said multiple physical coding modules include a first physical coding module;  
4 said first plurality of packet bytes includes a first subset of bytes of said first  
packet; and  
6 said first physical coding module is configured to:  
encode said first subset of bytes with a first start code if said first  
8 subset of bytes includes the initial byte of said first packet; and  
otherwise, encode said first subset of bytes without a start code.

116. (Previously Presented) The network interface device of claim  
2 34, wherein:  
said multiple physical coding modules include a first physical coding module;

4        said first plurality of packet bytes includes a first subset of bytes of said first  
packet; and  
6        said first physical coding module is configured to:  
         encode said first subset of bytes with a first start code if said first  
8        subset of bytes includes the initial byte of said first packet; and  
         otherwise, encode said first subset of bytes with a second start code  
10       different from said first start code.

117. (Previously Presented)        The network interface device of claim  
2    34, wherein:  
         said multiple physical coding modules include a first physical coding module;  
4       said first plurality of packet bytes includes a last subset of bytes of said first  
packet; and  
6       said first physical coding module is configured to:  
         encode said last subset of bytes with a first end code if said last subset  
8       of bytes includes the final byte of said first packet; and  
         otherwise, encode said last subset of bytes without an end code.

118. (Previously Presented)        The network interface device of claim  
2    34, wherein:  
         said multiple physical coding modules include a first physical coding module;  
4       said first plurality of packet bytes includes a last subset of bytes of said first  
packet; and  
6       said first physical coding module is configured to:  
         encode said last subset of bytes with a first end code if said last subset  
8       of bytes includes the final byte of said first packet; and  
         otherwise, encode said last subset of bytes with a second end code  
10       different from said first end code.

119. (Previously Presented)        The method of claim 28, wherein said  
2    decoding comprises:  
         decoding a first start code in a one of said sets of bytes, said one set of bytes  
4       containing an initial byte of the communication;  
         wherein no other set of bytes includes a start code.

120. (Previously Presented) The method of claim 28, wherein said  
2 decoding comprises:  
decoding a first start code in one of said sets of bytes, said one set of bytes  
4 containing an initial byte of the communication; and  
decoding a second start code in a different set of bytes, said second start code  
6 differing from said first start code.

121. (Previously Presented) The method of claim 28, wherein said  
2 decoding comprises:  
decoding a first end code in one of said sets of bytes, said one set of bytes  
4 containing a final byte of the communication;  
wherein no other set of bytes includes an end code.

122. (Previously Presented) The method of claim 28, wherein said  
2 decoding comprises:  
decoding a first end code in one of said sets of bytes, said one set of bytes  
4 containing a final byte of the communication; and  
decoding a second end code in a different set of bytes, said second end code  
6 differing from said first end code.

123. (Previously Presented) The method of claim 4, wherein said  
2 sending a first portion of said communication comprises:  
encoding said first portion with a first start code if said first portion includes  
4 the initial element of said communication.

124. (Previously Presented) The method of claim 123, wherein said  
2 sending a first portion of said communication further comprises:  
encoding said first portion without a start code if said first portion does not  
4 include said initial element of said communication.

125. (Previously Presented) The method of claim 123, wherein said  
2 sending a first portion of said communication further comprises:  
encoding said first portion with a second start code, different from said first

4 start code, if said first portion does not include said initial element of said  
communication.

126. (Previously Presented) The method of claim 4, wherein said  
2 sending a second portion of said communication comprises:  
encoding said second portion with a first end code if said second portion  
4 includes the final element of said communication.

127. (Previously Presented) The method of claim 123, wherein said  
2 sending a second portion of said communication further comprises:  
encoding said second portion without an end code if said second portion does  
4 not include said final element of said communication.

128. (Previously Presented) The method of claim 123, wherein said  
2 sending a second portion of said communication further comprises:  
encoding said second portion with a second end code, different from said first  
4 end code, if said second portion does not include said final element of said  
communication.

129. (Previously Presented) The method of claim 1, wherein said  
2 sending a first portion of said communication comprises:  
encoding said first portion of said communication with a first start code if said  
4 first portion of said communication includes the initial byte of said communication.

130. (Previously Presented) The method of claim 129, wherein said  
2 sending a first portion of said communication further comprises:  
encoding said first portion of said communication with a second start code,  
4 different from said first start code, if said first portion of said communication does not  
include the initial byte of said communication.

131. (Previously Presented) The method of claim 129, wherein said  
2 sending a first portion of said communication further comprises:  
encoding said first portion of said communication without a start code if said  
4 first portion of said communication does not include the initial byte of said

communication.

132. (Previously Presented) The method of claim 1, wherein said  
2 sending a second portion of said communication comprises:  
encoding said second portion of said communication with a first end code if  
4 said second portion of said communication includes the final byte of said  
communication.

Cl Cont.  
133. (Previously Presented) The method of claim 132, wherein said  
2 sending a second portion of said communication further comprises:  
encoding said second portion of said communication with a second end code,  
4 different from said first end code, if said second portion of said communication does  
not include the final byte of said communication.

134. (Previously Presented) The method of claim 132, wherein said  
2 sending a second portion of said communication further comprises:  
encoding said second portion of said communication without an end code if  
4 said second portion of said communication does not include the final byte of said  
communication.

---